Title

MINOS

Physics Goals

- 1. "If no oscillations, then demonstrate this over as large an area of parameter space available to MINOS"
- 2. If oscillations occur then measure $\sin^2 2\square_{13} > 0.01$ at the 90% confidence level

Features

Production of a neutrino beam using the main ring at Fermilab and a hadron decay pipe of 675 m. Neutrino energy 1 to 25 GeV

A near detector that is an elongated octagon 3.8 m high and 4.8 m wide (total weight 0.98 metric kT, 0.1 kT fiducaial).290 m from decay pipe

A far detector at Soudan, 730 km from decay pipe and 710m below the surface. The detector is octangular, 31 m long and 8m wide. It contains 486 layers of 2.54 cm iron (total weight 5.4 metric kT, 3.3 kT fiducial) magnetized to 1.5 T

Expect 3000 neutrino CC events/kT/yr (no oscillations)

Expect 20 events/spill in near detector

Technological Challenges

Keeping within budget

Cosmic ray 270 Hz in near detector; 1 Hz in far detector

LBNL Contribution and Interest

None

Status

http://www-numi.fnal.gov/talks/Lehman_Jan02.ppt

Timeline

Beam into the detector (Fermilab Forecast) 1/2/05

Start operations (DOE Milestone) 9/30/05

Near detector complete and tested (DOE) 3/31/05; (Fermilab) 10/1/04

Far detector complete and tested (DOE) 4/25/04; (Fermilab) 9/9/03

http://www-numi.fnal.gov/talks/Lehman_Jan02.ppt

Location

Fermilab

Collaboration

31 Institutions

194 participants

Funding Sources

DOE

Resources, Links, and References

http://www-numi.fnal.gov/minwork/minoswk.html

Summary prepared by: Andrew Sessler AMSessler@LBL.GOV
Lawrence Berkeley Laboratory
510-486-4992